KANTILAL CHIMANLAL

AHMEDABAD SINCE-1913

BRONZE PRESSURE REDUCING VALVE

RUBBER DIAPHRAGM, FOR WATER / AIR SERVICE

SPECIFICATIONS

'SANT' Bronze Pressure Reducing Valve

Direct Spring Loaded

Rubber Diaphragm

Screwed Female Ends BSP

Suitable for Water/Air Service

Suitable for Maximum Inlet Pressure / Temperature = 250 Psig / 50°C

Reduced Outlet Pressure Ranges Available (Psig) = 5/60, 20/80 & 40/125 Psig

These valves conform to IS:97391 981

TESTING & CERTIFICATION

Hydraulic Test Pressure

500 Psig Hyd.

Performance Test is carried out on compressed air line Our Works' Test Certificate is furnished with every supply.


Note: These valves are approved by MUNICIPAL CORPORATION of GREATER MUMBAI for installation in multistorey buildings.

MATERIALS

Components	Material	Material Specification
Body, Bottom Cover, Drain Plug, Disc Holder, valve Stem & Spring Discs	Bronze / Gun Metal	IS : 318 Gr.LTB2
Diaphragm Cover & Adjusting Screw	Cast Iron	IS:210 Gr.FG200
Diaphragm & Valve Disc	Rubber	Synthetic
Springs	Spring Steel	EN44 or Equi
Tommy Bar & Fasteners	Mild Stee	IS:226

DIMENSIONS (In mm)

Nominal Size	L	н	В
15	76	155	60
20	110	165	75
25	115	175	85
32	140	220	95
40	140	220	95
50	170	315	130



KANTILAL CHIMANLAL 662/45, Kapasia Bazaar Railwaypura, Ahmedabad-3800 02 Gujarat (INDIA)

Ph.: +91 79 2217 0041 / 80 Fax: +91 79 2212 1863 Mobile: +91 98795 15172 E-mail : kc@kantilalchimanlal.net